

MPICH2 Installer's Guide*

Version 1.3a1

Mathematics and Computer Science Division

Argonne National Laboratory

William Gropp
Ewing Lusk
David Ashton
Pavan Balaji
Darius Buntinas
Ralph Butler
Anthony Chan
Dave Goodell
Jayesh Krishna
Guillaume Mercier
Rob Ross
Rajeev Thakur
Brian Toonen

February 11, 2010

*This work was supported by the Mathematical, Information, and Computational Sciences Division subprogram of the Office of Advanced Scientific Computing Research, SciDAC Program, Office of Science, U.S. Department of Energy, under Contract DE-AC02-06CH11357.

Contents

1	Introduction	1
2	Quick Start	1
2.1	Prerequisites	1
2.2	From A Standing Start to Running an MPI Program	2
2.3	Compiler Optimization Levels	6
2.4	Common Non-Default Configuration Options	7
2.4.1	The Most Important Configure Options	7
2.4.2	Using the Absoft Fortran compilers with MPICH2	8
2.5	Shared Libraries	9
2.6	What to Tell the Users	9
3	Migrating from MPICH1	9
3.1	Configure Options	9
3.2	Other Differences	10
4	Choosing the Communication Device	11
5	Installing and Managing Process Managers	11
5.1	hydra	12
5.2	mpd	12
5.2.1	Configuring mpd	12
5.2.2	System Requirements	13
5.2.3	Using mpd	13
5.2.4	Options for mpd	14
5.2.5	Running MPD on multi-homed systems	14

5.2.6	Running MPD as Root	15
5.2.7	Running MPD on SMP's	15
5.2.8	Security Issues in MPD	16
5.3	SMPD	17
5.3.1	Configuration	17
5.3.2	Usage and administration	18
5.4	gforker	18
6	Testing	19
7	Benchmarking	19
8	MPE	20
9	Windows Version	20
9.1	Binary distribution	20
9.2	Source distribution	21
9.3	cygwin	22
10	All Configure Options	22
A	Troubleshooting MPDs	27
A.1	Getting Started with mpd	27
A.1.1	Following the steps	28
A.2	Debugging host/network configuration problems	33
A.3	Firewalls, etc.	34

1 Introduction

This manual describes how to obtain and install MPICH2, the MPI-2 implementation from Argonne National Laboratory. (Of course, if you are reading this, chances are good that you have already obtained it and found this document, among others, in its `doc` subdirectory.) This *Guide* will explain how to install MPICH so that you and others can use it to run MPI applications. Some particular features are different if you have system administration privileges (can become “root” on a Unix system), and these are explained here. It is not necessary to have such privileges to build and install MPICH2. In the event of problems, send mail to `mpich-discuss@mcs.anl.gov`. Once MPICH2 is installed, details on how to run MPI jobs are covered in the *MPICH2 User’s Guide*, found in this same `doc` subdirectory.

MPICH2 has many options. We will first go through a recommended, “standard” installation in a step-by-step fashion, and later describe alternative possibilities.

2 Quick Start

In this section we describe a “default” set of installation steps. It uses the default set of configuration options, which builds the `sock` communication device and the `MPD` process manager, for languages C, C++, Fortran-77, and Fortran-90 (if those compilers exist), with compilers chosen automatically from the user’s environment, without tracing and debugging options. It uses the `VPATH` feature of `make`, so that the build process can take place on a local disk for speed.

2.1 Prerequisites

For the default installation, you will need:

1. A copy of the distribution, `mpich2.tar.gz`.
2. A C compiler.
3. A Fortran-77, Fortran-90, and/or C++ compiler if you wish to write MPI programs in any of these languages.

4. Any one of a number of Unix operating systems, such as IA32-Linux. MPICH2 is most extensively tested on Linux; there remain some difficulties on systems to which we do not currently have access. Our `configure` script attempts to adapt MPICH2 to new systems.

Configure will check for these prerequisites and try to work around deficiencies if possible. (If you don't have Fortran, you will still be able to use MPICH2, just not with Fortran applications.)

2.2 From A Standing Start to Running an MPI Program

Here are the steps from obtaining MPICH2 through running your own parallel program on multiple machines.

1. Unpack the tar file.

```
tar xzf mpich2.tar.gz
```

If your tar doesn't accept the `z` option, use

```
gunzip -c mpich2.tar.gz | tar xf -
```

Let us assume that the directory where you do this is `/home/you/libraries`. It will now contain a subdirectory named `mpich2-1.3a1`.

2. Choose an installation directory (the default is `/usr/local/bin`):

```
mkdir /home/you/mpich2-install
```

It will be most convenient if this directory is shared by all of the machines where you intend to run processes. If not, you will have to duplicate it on the other machines after installation. Actually, if you leave out this step, the next step will create the directory for you.

3. Choose a build directory. Building will proceed *much* faster if your build directory is on a file system local to the machine on which the configuration and compilation steps are executed. It is preferable that this also be separate from the source directory, so that the source directories remain clean and can be reused to build other copies on other machines.

```
mkdir /tmp/you/mpich2-1.3a1
```

4. Choose any configure options. See Section 2.4.1 for a description of the most important options to consider.
5. Configure MPICH2, specifying the installation directory, and running the `configure` script in the source directory:

```
cd /tmp/you/mpich2-1.3a1
/home/you/libraries/mpich2-1.3a1/configure \
-prefix=/home/you/mpich2-install |& tee c.txt
```

where the `\` means that this is really one line. (On `sh` and its derivatives, use `2>&1 | tee c.txt` instead of `|& tee c.txt`). Other configure options are described below. Check the `c.txt` file to make sure everything went well. Problems should be self-explanatory, but if not, send `c.txt` to `mpich-discuss@mcs.anl.gov`. The file `config.log` is created by `configure` and contains a record of the tests that `configure` performed. It is normal for some tests recorded in `config.log` to fail.

6. Build MPICH2:

```
make |& tee m.txt          (for csh and tcsh)
OR
make 2>&1 | tee m.txt      (for bash and sh)
```

This step should succeed if there were no problems with the preceding step. Check file `m.txt`. If there were problems, do a `make clean` and then run `make` again with `VERBOSE=1`

```
make VERBOSE=1 |& tee m.txt      (for csh and tcsh)
OR
make VERBOSE=1 2>&1 | tee m.txt  (for bash and sh)
```

and then send `m.txt` and `c.txt` to `mpich-discuss@mcs.anl.gov`.

7. Install the MPICH2 commands:

```
make install |& tee mi.txt
```

This step collects all required executables and scripts in the `bin` subdirectory of the directory specified by the `prefix` argument to `configure`.

(For users who want an install directory structure compliant to GNU coding standards (i.e., documentation files go to `${datarootdir}/doc/${PACKAGE}`, architecture independent read-only files go to `${datadir}/${PACKAGE}`), replace `make install` by

```
make install PACKAGE=mpich2-<version>
```

and corresponding `installcheck` step should be

```
make installcheck PACKAGE=mpich2-<version>
```

Setting `PACKAGE` in `make install` or `make installcheck` step is optional and unnecessary for typical MPI users.)

8. Add the `bin` subdirectory of the installation directory to your path:

```
setenv PATH /home/you/mpich2-install/bin:$PATH
```

for `csh` and `tcsh`, or

```
export PATH=/home/you/mpich2-install/bin:$PATH
```

for `bash` and `sh`. Check that everything is in order at this point by doing

```
which mpicc
which mpiexec
```

All should refer to the commands in the `bin` subdirectory of your install directory. It is at this point that you will need to duplicate this directory on your other machines if it is not in a shared file system such as NFS.

9. Check that you can reach these machines with `ssh` or `rsh` without entering a password. You can test by doing

```
ssh othermachine date
```

or

```
rsh othermachine date
```

If you cannot get this to work without entering a password, you will need to configure `ssh` or `rsh` so that this can be done.

10. Test the setup you just created:

```
mpiexec -f machinefile -n <number> hostname
```

The machinefile contains the list of hosts you want to run the executable on.

```
% cat machinefile
host1      # Run 1 process on host1
host2:4    # Run 4 processes on host2
host3:2    # Run 2 processes on host3
host4:1    # Run 1 process on host4
```

11. Now we will run an MPI job, using the `mpiexec` command as specified in the MPI-2 standard.

As part of the build process for MPICH2, a simple program to compute the value of π by numerical integration is created in the `mpich2-1.3a1/examples` directory. If the current directory is the top level MPICH2 build directory, then you can run this program with

```
mpiexec -n 5 -f machinefile ./examples/cpi
```

The `cpi` example will tell you which hosts it is running on.

There are many options for `mpiexec`, by which multiple executables can be run, hosts can be specified (as long as they are in the mpd ring), separate command-line arguments and environment variables can be passed to different processes, and working directories and search paths for executables can be specified. Do

```
mpiexec --help
```

for details. A typical example is:


```
mpiexec -f machinefile -n 1 ./master : -n 19 ./slave
```

to ensure that the process with rank 0 runs on your workstation.

The arguments between ‘:’s in this syntax are called “argument sets,” since they apply to a set of processes. More arguments are described in the *User’s Guide*.

If you have completed all of the above steps, you have successfully installed MPICH2 and run an MPI example.

2.3 Compiler Optimization Levels

MPICH2 can be configured with two sets of compiler flags: CFLAGS, CXXFLAGS, FFLAGS, F90FLAGS (abbreviated as xFLAGS) and MPICH2LIB_CFLAGS, MPICH2LIB_CXXFLAGS, MPICH2LIB_FFLAGS, MPICH2LIB_F90FLAGS (abbreviated as MPICH2LIB_xFLAGS) for compilation; LDFLAGS and MPICH2LIB_LDFLAGS for linking. All these flags can be set as part of configure command or through environment variables. (CPPFLAGS stands for C preprocessor flags, which should NOT be set)

Both xFLAGS and MPICH2LIB_xFLAGS affect the compilation of the MPICH2 libraries. However, only xFLAGS is appended to MPI wrapper scripts, mpicc and friends.

MPICH2 libraries are built with default compiler optimization, -O2, which can be modified by --enable-fast configure option. For instance, --disable-fast disables the default optimization option. --enable-fast=O_n sets default compiler optimization as -O_n. For more details of --enable-fast, see the output of “configure --help”. Any other complicated optimization flags for MPICH2 libraries have to be set through MPICH2LIB_xFLAGS. CFLAGS and friends are empty by default.

For example, to build a “production” MPICH2 environment with -O3 for all language bindings, one can simply do

```
./configure --enable-fast=O3
```

or

```
./configure --disable-fast MPICH2LIB_CFLAGS=-O3 \
```

```

MPICH2LIB_FFLAGS=-O3 \
MPICH2LIB_CXXFLAGS=-O3 \
MPICH2LIB_F90FLAGS=-O3

```

This will cause the MPICH2 libraries to be built with -O3, and -O3 will not be included in the mpicc and other MPI wrapper script.

There are certain compiler flags that should not be used with MPICH2's configure, e.g. gcc's -Werror which would confuse configure and cause certain configure tests to fail to detect the correct system features. To use -Werror in building MPICH2 libraries, you can pass the compiler flags during the make step through the Makefile variable, `MPICH2_MAKE_CFLAGS` as follows:

```
make VERBOSE=1 MPICH2_MAKE_CFLAGS="-Wall -Werror"
```

(assume CC is set to gcc). The content of `MPICH2_MAKE_CFLAGS` is appended to the `CFLAGS` in almost all Makefiles.

2.4 Common Non-Default Configuration Options

A list of `configure` options is found in Section 10. Here we comment on some of them.

2.4.1 The Most Important Configure Options

—prefix Set the installation directories for MPICH2.

—enable-debuginfo Provide access to the message queues for debuggers such as Totalview.

—enable-g Build MPICH2 with various debugging options. This is of interest primarily to MPICH2 developers. The options

```
--enable-g=dbg,mem,log
```

are recommended in that case.

—enable-fast Configure MPICH2 for fastest performance at the expense of error reporting and other program development aids. This is recommended only for getting the best performance out of proven production applications, and for benchmarking.

- enable-sharedlibs** Build MPICH2 with shared libraries. For example,
 - `--enable-sharedlibs=gcc` for standard gcc on Linux
 - `--enable-sharedlibs=osx-gcc` for Mac OS X or
 - `--enable-sharedlibs=solaris-cc` for cc on Solaris
- with-pm** Select the process manager. The default is `hydra`; also useful are `gforker` and `mpd`. You can build with all three process managers by specifying
 - `--with-pm=hydra:mpd:gforker`
- without-mpe** Configure MPICH2 without the MPE package of program development tools (including the Jumpshot performance viewer)
- with-java** Set the location of Java installation. This option is necessary only if the default Java installation in your PATH does not contain a valid Java installation for Jumpshot, e.g.
 - `--with-java=/opt/jdk1.6.0`

2.4.2 Using the Absoft Fortran compilers with MPICH2

For best results, it is important to force the Absoft Fortran compilers to make all routine names monospace. In addition, if lower case is chosen (this will match common use by many programs), you must also tell the the Absoft compiles to append an underscore to global names in order to access routines such as `getarg` (`getarg` is not used by MPICH2 but is used in some of the tests and is often used in application programs). We recommend configuring MPICH2 with the following options

```
setenv F77 f77
setenv FFLAGS "-f -N15"
setenv F90FLAGS "-YALL_NAMES=LCS -YEXT_SFX=_"

./configure ....
```

2.5 Shared Libraries

Shared libraries are currently only supported for gcc on Linux and Mac OS X and for cc on Solaris. To have shared libraries created when MPICH2 is built, specify the following when MPICH2 is configured:

```
configure --enable-sharedlibs=gcc      (on Linux)
configure --enable-sharedlibs=osx-gcc  (on Mac OS X)
configure --enable-sharedlibs=solaris-cc (on Solaris)
```

2.6 What to Tell the Users

Now that MPICH2 has been installed, the users have to be informed of how to use it. Part of this is covered in the *User's Guide*. Other things users need to know are covered here.

3 Migrating from MPICH1

MPICH2 is an all-new rewrite of MPICH1. Although the basic steps for installation have remained the same (`configure`, `make`, `make install`), a number of things have changed. In this section we attempt to point out what you may be used to in MPICH1 that are now different in MPICH2.

3.1 Configure Options

The arguments to `configure` are different in MPICH1 and MPICH2; the *Installer's Guide* discusses `configure`. In particular, the newer `configure` in MPICH2 does not support the `-cc=<compiler-name>` (or `-fc`, `-c++`, or `-f90`) options. Instead, many of the items that could be specified in the command line to configure in MPICH1 must now be set by defining an environment variable. E.g., while MPICH1 allowed

```
./configure -cc=pgcc
```

MPICH2 requires

```
setenv CC pgcc
```

(or `export CC=pgcc` for `ksh` or `CC=pgcc ; export CC` for strict `sh`) before `./configure`. Basically, every option to the MPICH-1 `configure` that does not start with `--enable` or `--with` is not available as a `configure` option in MPICH2. Instead, environment variables must be used. This is consistent (and required) for use of version 2 GNU `autoconf`.

3.2 Other Differences

Other differences between MPICH1 and MPICH2 include the handling of process managers and the choice of communication device.

For example, the new process managers have a new format and slightly different semantics for the `-machinefile` option. Assume that you type this data into a file named `machfile`:

```
bp400:2
bp401:2
bp402:2
bp403:2
```

If you then run a parallel job with this machinefile, you would expect ranks 0 and 1 to run on bp400 because it says to run 2 processes there before going on to bp401. Ranks 2 and 3 would run on bp401, and rank 4 on bp402, e.g.:

```
mpiexec -l -machinefile machfile -n 5 hostname
```

produces:

```
0: bp400
1: bp400
2: bp401
3: bp401
4: bp402
```

4 Choosing the Communication Device

MPICH2 is designed to be build with many different communication devices, allowing an implementation to be tuned for different communication fabrics. A simple communication device, known as “ch3” (for the third version of the “channel” interface) is provided with MPICH2 and is the default choice.

The ch3 device itself supports a variety of communication methods. These are specified by providing the name of the method after a colon in the `--with-device` configure option. For example, `--with-device=ch3:ssm` selects the socket plus shared memory method. The supported methods include:

ch3:nemesis This method is our new, high performance method. It has been made the default communication channel starting the 1.1 release of MPICH2. It uses shared-memory to send messages between processes on the same node and the network for processes between nodes. Currently sockets and Myrinet-MX are supported networks. It supports `MPI_THREAD_MULTIPLE` and other levels of thread safety.

ch3:sock This method uses sockets for all communications between processes. It supports `MPI_THREAD_MULTIPLE` and other levels of thread safety.

ch3:ssm This method uses sockets between nodes and shared memory within a node.

ch3:shm This method only uses shared memory and only works within a single SMP. It does not support the MPI dynamic process routines such as `MPI_Comm_spawn`.

Most installations should use the default **ch3:nemesis** method for best performance. For platforms that are not supported by nemesis, the **ch3:sock** method is suggested.

5 Installing and Managing Process Managers

MPICH2 has been designed to work with multiple process managers; that is, although you can start MPICH2 jobs with `mpiexec`, there are different

mechanisms by which your processes are started. An interface (called PMI) isolates the MPICH2 library code from the process manager. Currently three process managers are distributed with MPICH2

hydra This is the default process manager that natively uses the existing daemons on the system such as ssh, slurm, pbs.

mpd This is the traditional process manager used in MPICH2. It consists of a ring of daemons.

smpd This one can be used for both Linux and Windows. It is the only process manager that supports the Windows version of MPICH2.

gforker This is a simple process manager that creates all processes on a single machine. It is useful for both debugging and on shared memory multiprocessors.

5.1 hydra

hydra is the default process manager that launches processes using the native daemons present on the system such as ssh, slurm, pbs, etc. To configure with the hydra process manager, use

```
configure --with-pm=hydra ...
```

5.2 mpd

5.2.1 Configuring mpd

The mpd process manager can be explicitly chosen at configure time by adding

```
--with-pm=mpd
```

to the `configure` arguments. This is not necessary, since mpd is the default.

5.2.2 System Requirements

`mpd` consists of a number of components written in Python. The `configure` script should automatically find a version of python in your `PATH` that has all the features needed to run `mpd`. If for some reason you need to pick a specific version of Python for `mpd` to use, you can do so by adding

```
--with-python=<fullpathname of python interpreter>
```

to your `configure` arguments. If your system doesn't have Python, you can get the latest version from <http://www.python.org>. Most Linux distributions include a moderately current version of Python. MPD requires release 2.2 or later.

The `mpd` process manager supports the use of the TotalView parallel debugger from Etnus. If `totalview` is in your `PATH` when MPICH2 is configured, then an interface module will be automatically compiled, linked, and installed so that you can use TotalView to debug MPICH jobs (See the *User's Guide* under "Debugging". You can also explicitly enable or disable this capability with `--enable-totalview` or `--disable-totalview` as arguments to `configure`.

5.2.3 Using mpd

In Section 2.2 you installed the `mpd` ring. Several commands can be used to use, test, and manage this ring. You can find out about them by running `mpdhelp`, whose output looks like this:

The following `mpd` commands are available. For usage of any specific one, invoke it with the single argument `--help`.

<code>mpd</code>	start an <code>mpd</code> daemon
<code>mpdtrace</code>	show all <code>mpd</code> 's in ring
<code>mpdboot</code>	start a ring of daemons all at once
<code>mpdringtest</code>	test how long it takes for a message to circle the ring
<code>mpdallexit</code>	take down all daemons in ring
<code>mpdcleanup</code>	repair local Unix socket if ring crashed badly
<code>mpdlistjobs</code>	list processes of jobs (-a or --all: all jobs for all users)
<code>mpdkilljob</code>	kill all processes of a single job
<code>mpdsigjob</code>	deliver a specific signal to the application processes of a job

`mpiexec` start a parallel job

Each command can be invoked with the `--help` argument, which prints usage information for the command without running it.

So for example, to see a complete list of the possible arguments for `mpdboot`, you would run

```
mpdboot --help
```

5.2.4 Options for mpd

`-help` causes mpd to print a list and description of all options

In addition to the cmd-line options, mpd will also check for presence of the environment variable `MPICH_PORT_RANGE` (note `MPICH` instead of `MPD`) and use only the ports in that range for listening sockets. The range is separated by a colon, e.g., `2000:8000`.

5.2.5 Running MPD on multi-homed systems

If you plan to use one or more multi-homed systems, it is of course useful if the default hostname is associated with the interface that mpd will need to use for communications. If not however, you can cause mpd to use a specific interface by using the `--ifhn` (interface-hostname) option, e.g.:

```
n1% mpd --ifhn=192.168.1.1 &
```

If you then run `mpiexec` on `n1` connecting to that mpd, the `mpiexec` will use the same `ifhn` for communications with remote processes that connect back to it. `mpiexec` will also accept a `-ifhn` option (`mpiexec -help`) in the unlikely event that you wish it to use a separate interface from the mpd.

`mpdboot` can also designate the `ifhn` to be used by both the local and remote mpds which it starts, e.g.:

```
n1% mpdboot --totalnum=3 --ifhn=192.168.1.1
```

where `mpd.hosts` contains:

```
n2 ifhn=192.168.1.2
n3 ifhn=192.168.1.3
```

will start one mpd locally, one on n2 and one on n3. Each will use the respectively designated ifhn.

5.2.6 Running MPD as Root

MPD can run as root to support multiple users simultaneously. To do this, it easiest to simply do the “make install” in the mpd sub-directory as root. This will cause the `mpdroot` program to be installed in the bin directory with `setuid-root` permissions. Individual users then have the option of starting and using their own mpd rings, or they can run with a ring started by root. To use root’s ring, they must use an option named `MPD_USE_ROOT_MPD`. This option may either be set as an environment variable or they can set it in their own `.mpd.conf` file, e.g.:

```
MPD_USE_ROOT_MPD=1
```

When root starts the mpds in the ring, the procedure is the same as for a regular user except that root’s configuration file is in `/etc/mpd.conf` (note that there is no leading dot in the file name).

5.2.7 Running MPD on SMP’s

Typically one starts one `mpd` on each host. When a job is started with `mpiexec` without any particular host specification, the processes are started on the ring of hosts one at a time, in round-robin fashion until all the processes have been started. Thus, if you start a four-process job on a ring of two machines, `hosta` and `hostb`, then you will find ranks 0 and 2 on `hosta` and ranks 1 and 3 on `hostb`. This might not be what you want, especially if the machines are SMP’s and you would like to have consecutive ranks on the same machine as much as possible. If you tell the `mpd` how many cpus it has to work with by using the `--ncpus` argument, as in

```
mpd --ncpus=2
```

then the number of processes started the first time the startup message circles the ring will be determined by this argument. That is, in the above

four-process example, ranks 0 and 1 will be on `hosta` and ranks 2 and 3 will be on `hostb`. This effect only occurs the first time around the ring. That is if you start a six-process job on this ring (two `mpd`'s, each started with `--ncpus=2`) you will get processes 0, 1, and 4 on `hosta` and 2, 3, and 5 on `hostb`. This is for load-balancing purposes. (It is assumed that you do not want 0, 1, 4, and 5 on `hosta` and only 2 and 3 on `hostb`; if that is what you *do* want, you can control process placement explicitly on the `mpiexec` command, as described in the *User's Guide*.

5.2.8 Security Issues in MPD

Since the `mpd` process manager allows the remote execution of processes, it needs to incorporate security features that prevent inappropriate or malicious process creation by someone without permission to do so. In this section we describe how `mpd` deals with a number of security issues.

The first issue is the starting of the `mpd` processes themselves. This is done either by the user logging into each machine starting each `mpd` process “by hand,” or else by using the `mpdboot` program. `mpdboot` uses `ssh` by default, although the less secure `rsh` can be used if the user chooses.

The next issue occurs when a single new `mpd` joins a ring of existing `mpd`'s. This occurs during `mpdboot`, or can occur later if the user wishes to expand an existing ring. In this situation a “challenge-response” protocol is followed. A user must have the same `secretword` set in his `.mpd.conf` file on each machine. This file must be readable only by the user starting the `mpd`; otherwise the `mpd` will refuse to read it. When `mpd` A wishes to join an existing ring by connecting to `mpd` B, which is already in the ring, at the port B is listening on, the following sequence of events occurs:

1. B temporarily accepts the connection.
2. B seeds the random number generator with the high-resolution part of the time of day, generates a random number, and sends it to A.
3. A concatenates the random number with the value of `secretword` in `.mpd.conf`, encrypts it with md5, and sends the encrypted result to B.
4. Meanwhile, B encrypts the (same) random number concatenated with its value of `secretword`.

5. When B receives the encrypted value from A, it compares the encrypted value with its own.
6. If the values match, A is allowed to join the ring; otherwise the connection is closed.

Note that the secret word is never sent over the connection in the clear, and the use of the time of day means that there will be no repeating pattern of challenges to be observed.

The third issue concerns how `mpiexec` connects to the local `mpd`. This is done through a Unix socket in `/tmp` rather than through an INET socket. Thus security is preserved through the security of the file system.

Once connections are established, the messages that are sent over them are not encrypted. However, no security information is sent over these connections.

5.3 SMPD

5.3.1 Configuration

You may add the following configure options, `--with-pm=smpd`, to build and install the `smpd` process manager. The process manager, `smpd`, will be installed to the `bin` sub-directory of the installation directory of your choice specified by the `--prefix` option.

`smpd` process managers run on each node as stand-alone daemons and need to be running on all nodes that will participate in MPI jobs. `smpd` process managers are not connected to each other and rely on a known port to communicate with each other. Note: If you want multiple users to use the same nodes they must each configure their `smpds` to use a unique port per user.

`smpd` uses a configuration file to store settings. The default location is `~/.smpd`. This file must not be readable by anyone other than the owner and contains at least one required option - the access passphrase. This is stored in the configuration file as `phrase=<phrase>`. Access to running `smpds` is authenticated using this passphrase and it must not be your user password.

5.3.2 Usage and administration

Users will start the `smpd` daemons before launching mpi jobs. To get an `smpd` running on a node, execute

```
smpd -s
```

Executing this for the first time will prompt the user to create a `~/.smpd` configuration file and passphrase if one does not already exist.

Then users can use `mpiexec` to launch MPI jobs.

All options to `smpd`:

`smpd -s`

Start the `smpd` service/daemon for the current user. You can add `-p <port>` to specify the port to listen on. All `smpds` must use the same port and if you don't use the default then you will have to add `-p <port>` to `mpiexec` or add the `port=<port>` to the `.smpd` configuration file.

`smpd -r`

Start the `smpd` service/daemon in root/multi-user mode. This is not yet implemented.

`smpd -shutdown [host]`

Shutdown the `smpd` on the local host or specified host. Warning: this will cause the `smpd` to exit and no `mpiexec` or `smpd` commands can be issued to the host until `smpd` is started again.

5.4 gforker

`gforker` is a simple process manager that runs all processes on a single node; it's version of `mpiexec` uses the system `fork` and `exec` calls to create the new processes. To configure with the `gforker` process manager, use

```
configure --with-pm=gforker ...
```

6 Testing

Once MPICH2 has been installed, you can test it by running some of the example programs in the `examples` directory. A more thorough test can be run with the command `make testing`. This will produce a summary on standard output, along with an XML version of the test results in `mpich2/test/mpi`. In addition, running `make testing` from the top-level (`mpich2`) directory will run tests of the commands, such as `mpicc` and `mpiexec`, that are included with MPICH2.

Other MPI test suites are available from <http://www.mcs.anl.gov/mpi/mpi-test/tsuite.html>. As part of the MPICH2 development, we run the MPICH1, MPICH2, C++, and Intel test suites every night and post the results on <http://www.mcs.anl.gov/mpi/mpich1/micronotes/mpich2-status/>. Other tests are run on an occasional basis.

7 Benchmarking

There are many benchmarking programs for MPI implementations. Three that we use are `mpptest` (<http://www.mcs.anl.gov/mpi/mpptest>), `netpipe` (<http://www.scl.ameslab.gov/netpipe>), and `SkaMPI` (<http://liinwww.ira.uka.de/~skampi>). Each of these has different strengths and weaknesses and reveals different properties of the MPI implementation.

In addition, the MPICH2 test suite contains a few programs to test for performance artifacts in the directory `test/mpi/perf`. An example of a performance artifact is markedly different performance for the same operation when performed in two different ways. For example, using an MPI datatype for a non-contiguous transfer should not be much slower than packing the data into a contiguous buffer, sending it as a contiguous buffer, and then unpacking it into the destination buffer. An example of this from the MPI-1 standard illustrates the use of MPI datatypes to transpose a matrix “on the fly,” and one test in `test/mpi/perf` checks that the MPI implementation performs well in this case.

8 MPE

MPICH2 comes with the same MPE (Multi-Processing Environment) tools that are included with MPICH1. These include several trace libraries for recording the execution of MPI programs and the Jumpshot and SLOG tools for performance visualization. The MPE tools are built and installed by default and should be available without requiring any additional steps. The installation of MPE is documented in `mpich2/src/mpe2/INSTALL` and the usage of MPE is documented in `mpich2/src/mpe2/README` and MPICH2 user's guide.

9 Windows Version

9.1 Binary distribution

The Windows binary distribution uses the Microsoft Installer. Download and execute `mpich2-1.x.xxx.msi` to install the binary distribution. The default installation path is `C:\Program Files\MPICH2`. You must have administrator privileges to install `mpich2-1.x.xxx.msi`. The installer installs a Windows service to launch MPICH applications and only administrators may install services. This process manager is called `smpd.exe`. Access to the process manager is passphrase protected. The installer asks for this passphrase. Do not use your user password. The same passphrase must be installed on all nodes that will participate in a single MPI job.

Under the installation directory are three sub-directories: `include`, `bin`, and `lib`. The `include` and `lib` directories contain the header files and libraries necessary to compile MPI applications. The `bin` directory contains the process manager, `smpd.exe`, and the MPI job launcher, `mpiexec.exe`. The dlls that implement MPICH2 are copied to the Windows system32 directory.

You can install MPICH in unattended mode by executing

```
msiexec /q /I mpich2-1.x.xxx.msi
```

The `smpd` process manager for Windows runs as a service that can launch jobs for multiple users. It does not need to be started like the unix version

does. The service is automatically started when it is installed and when the machine reboots. `smpd` for Windows has additional options:

```
smpd -start
    Start the Windows smpd service.

smpd -stop
    Stop the Windows smpd service.

smpd -install
    Install the smpd service.

smpd -remove
    Remove the smpd service.

smpd -register_spn
    Register the Service Principal Name with the domain controller. This
    command enables passwordless authentication using kerberos. It must
    be run on each node individually by a domain administrator.
```

9.2 Source distribution

In order to build MPICH2 from the source distribution under Windows, you must have MS Developer Studio .NET 2003 or later, perl and optionally Intel Fortran 8 or later.

- Download `mpich2-1.x.y.tar.gz` and unzip it.
- Bring up a Visual Studio Command prompt with the compiler environment variables set.
- Run `winconfigure.wsf`. If you don't have a Fortran compiler add the `--remove-fortran` option to `winconfigure` to remove all the Fortran projects and dependencies. Execute `winconfigure.wsf /?` to see all available options.
- open `mpich2\mpich2.sln`
- build the `ch3sockRelease mpich2` solution
- build the `ch3sockRelease mpich2s` project

- build the Release mpich2 solution
- build the fortRelease mpich2 solution
- build the gfortRelease mpich2 solution
- build the sfortRelease mpich2 solution
- build the channel of your choice. The options are **sock**, **shm**, and **ssm**. The shm channel is for small numbers of processes that will run on a single machine using shared memory. The shm channel should not be used for more than about 8 processes. The **ssm** (sock shared memory) channel is for clusters of smp nodes. This channel should not be used if you plan to over-subscribe the CPU's. If you plan on launching more processes than you have processors you should use the default **sock** channel. The **ssm** channel uses a polling progress engine that can perform poorly when multiple processes compete for individual processors.

9.3 cygwin

MPICH2 can also be built under **cygwin** using the source distribution and the Unix commands described in previous sections. This will not build the same libraries as described in this section. It will build a “Unix” distribution that runs under **cygwin**.

10 All Configure Options

Here is a list of all the configure options currently recognized by the top-level configure. It is the MPICH-specific part of the output of

```
configure --help
```

Not all of these options may be fully supported yet.

```
--disable-option-checking  ignore unrecognized --enable/--with options
--disable-FEATURE          do not include FEATURE (same as --enable-FEATURE=no)
--enable-FEATURE[=ARG]    include FEATURE [ARG=yes]
--enable-cache             - Turn on configure caching
```

```

--enable-echo - Turn on strong echoing. The default is enable=no.
--enable-coverage - Turn on coverage analysis using gcc and gcov
--enable-dynamiclibs - Enable the use of dynamic libraries by the devices
                      that support them
--enable-error-checking=level - Control the amount of error checking.
    no - no error checking
    runtime - error checking controllable at runtime through environment
              variables
    all - error checking always enabled
--enable-error-messages=level - Control the amount of detail in error messages.
    all - Maximum amount of information
    generic - Only generic messages (no information about the specific
              instance)
    class - One message per MPI error class
    none - No messages
--enable-timing=level - Control the amount of timing information
                      collected by the MPICH implementation.
    none - Collect no data (default)
    all - Collect lots of data
    runtime - Runtime control of data collected

--enable-g=option - Control the level of debugging support in the
                   MPICH implementation. option is a list of comma
                   separated names including
    none - No debugging
    handle - Trace handle operations
    handlealloc - Trace handle allocations
    dbg - Add compiler flag, -g, to CFLAGS, CXXFLAGS FFLAGS and F90FLAGS.
    debug - Synonym for dbg
    log - Enable debug event logging
    mem - Memory usage tracing
    meminit - Preinitialize memory associated structures and unions to
              eliminate access warnings from programs like valgrind
    memarena - Check for overwrite errors in memory allocation arena
    mutex - Enable error checking on pthread mutexes
    mutexnesting - Check for non-nesting of mutexes
    nesting - Check for proper nesting values
    fine-grain-nesting - Perform a fine-grain nesting check on exit
    all - All of the above choices
--enable-fast=option - Control the level of fast execution in the
                     MPICH implementation. option is a list of
                     comma separated names including
    O<n> - Appends default optimization flags, -O<n>, to all internal
          compiler flags, i.e. MPICH2LIB_CFLAGS, MPICH2LIB_CXXFLAGS,
          MPICH2LIB_FFLAGS, and MPICH2LIB_F90FLAGS.

```

```

defopt    - Default compiler optimization -O2 for all language bindings,
            i.e. --enable-fast=O2, when neither --enable-fast
            nor --disable-fast is specified.
nochkmsg  - No error checking, i.e. --disable-error-checking
notiming  - No timing collection, i.e. --disable-timing.
ndebug    - Appends -DNDEBUG to internal CFLAGS, i.e. MPICH2LIB_CFLAGS.
all|yes   - "defopt", "nochkmsg", "notiming" and "ndebug" are enabled
            when --enable-fast is specified without any option.
none      - None of above options, i.e. --disable-fast.

--enable-check-compiler-flags -- enable the checks for all compiler
                                options, xxxFLAGS, MPICH2_xxxFLAGS.
                                Default is on.

--enable-f77 - Enable Fortran 77 bindings
--enable-f90 - Enable Fortran 90 bindings
--enable-cxx - Enable C++ bindings
--enable-romio - Enable ROMIO MPI I/O implementation
--enable-debuginfo - Enable support for debuggers
--enable-mpicoll - Enable support for SMP/multi-core aware collectives
--enable-mpi - Enable support for pipelined collectives
--enable-nmpi-as-mpi - Use MPI rather than PMPI routines for MPI
                      routines, such as the collectives, that may be
                      implemented in terms of other MPI routines

--enable-mpe - Build the MPE (MPI Parallel Environment) routines
--enable-threads=level - Control the level of thread support in the
                        MPICH implementation. The following levels
                        are supported.
default              - Choose thread level at runtime based on parameters
                        passed to MPI_Init_thread (default)
single               - No threads (MPI_THREAD_SINGLE)
funneled             - Only the main thread calls MPI (MPI_THREAD_FUNNELED)
serialized           - User serializes calls to MPI (MPI_THREAD_SERIALIZED)
multiple(:impl)      - Fully multi-threaded (MPI_THREAD_MULTIPLE)
    The following implementations are supported.
        global_mutex - a single global lock guards access to all
                        MPI functions.
    The default implementation is global_mutex.

```

For the ch3:sock and ch3:nemesis channels, a separate build is no longer needed for thread-multiple. It is compiled by default and is selectable at run time with MPI_Init_thread. If MPI_Init_thread is not called, the default is funneled. For other channels, the --enable-threads option is not supported

currently, and the default is funneled.

```
--enable-thread-cs=type - Choose the method used for critical
                           sections and other atomic updates when
                           multiple threads are present.  Values may
                           be global (default), brief-global,
                           per-object, lock-free

--enable-refcount=type - Choose the method for ensuring atomic
                           updates to the reference counts for MPI
                           objects.  Values may be lock, lock-free,
                           none.  The default depends on the thread-cs
                           choice; for global it is none (because none
                           is required), for brief-global and per-object
                           it is lock, and for lock-free it is
                           lock-free

--enable-mutex-timing - calculate the time spent waiting on mutexes.
--enable-handle-allocation=type - Choose the method used for
                                   allocating MPI object handles.
                                   Values may be 'tls' for thread-local
                                   storage or 'mutex' for simple
                                   locking.  'mutex' is the default.

--enable-weak-symbols - Use weak symbols to implement PMPI routines (default)
--enable-strict - Turn on strict debugging with gcc
--enable-sharedlibs=kind - Enable shared libraries.  kind may be
    gcc          - Standard gcc and GNU ld options for creating shared libraries
    osx-gcc      - Special options for gcc needed only on OS/X
    solaris-cc   - Solaris native (SPARC) compilers for 32 bit systems
    cygwin-gcc   - Special options for gcc needed only for cygwin
    none        - same as --disable-sharedlibs
Only gcc, osx-gcc, and solaris-cc are currently supported

--enable-dependencies - Generate dependencies for sourcefiles.  This
                        requires that the Makefile.in files are also created
                        to support dependencies (see maint/updatefiles)
--enable-alloca - Use alloca to allocate temporary memory if available
--enable-timer-type=name - Select the timer to use for MPI_Wtime and
                           internal timestamps.
    gethrtime    - Solaris timer (Solaris systems only)
    clock_gettime - Posix timer (where available)
    gettimeofday - Most Unix systems
    linux86_cycle - Linux x86; returns cycle counts, not time in seconds*
    linuxalpha_cycle - Like linux86_cycle, but for Linux Alpha*
```

```
--with-thread-package=package - Thread package to use.  Supported thread
                             packages include:
    posix or pthreads - POSIX threads
```

```
solaris - Solaris threads (Solaris OS only)
none - no threads
```

If the option is not specified, the default package is `${MPIU_THREAD_DEFAULT}`.
If the option is specified, but a package is not given, then the default is `posix`.

Notes on the configure options. The `--with-htmldir` and `--with-docdir` options specify the directories into which the documentation will be installed by `make install`.

A Troubleshooting MPDs

A.1 Getting Started with mpd

`mpd` stands for multi-purpose daemon. We sometimes use the term `mpd` to refer to the combination of the `mpd` daemon and its helper programs that collectively form a process management system for executing parallel jobs, including `mpich` jobs. The `mpd` daemon must run on each host where you wish to execute parallel programs. The `mpd` daemons form a ring to facilitate rapid process startup. Even a single `mpd` on a single host forms a loop. Therefore, each host must be configured in such a way that the `mpds` can connect to each other and pass messages via sockets.

It can be rather tricky to configure one or more hosts in such a way that they adequately support client-server applications like `mpd`. In particular, each host must not only know its own name, but must identify itself correctly to other hosts when necessary. Further, certain information must be readily accessible to each host. For example, each host must be able to map another host's name to its IP address. In this section, we will walk slowly through a series of steps that will help to ensure success in running `mpds` on a single host or on a large cluster.

If you can `ssh` from each machine to *itself*, and from each machine to each other machine in your set (and back), then you probably have an adequate environment for `mpd`. However, there may still be problems. For example, if you are blocking all ports except the ports used by `ssh/sshhd`, then `mpd` will still fail to operate correctly.

To begin using `mpd`, the sequence of steps that we recommend is this:

1. get one mpd working alone on a first test node
2. get one mpd working alone on a second test node
3. get two new mpds to work together on the two test nodes
4. boot two new mpds on the two test nodes via mpdboot

A.1.1 Following the steps

1. Install mpich2, and thus mpd.
2. Make sure the mpich2 bin directory is in your path. Below, we will refer to it as MPDDIR.
3. Kill old mpd processes. If you are coming to this guide from elsewhere, e.g. a Quick Start guide for mpich2, because you encountered mpd problems, you should make sure that all mpd processes are terminated on the hosts where you have been testing. `mpdallexit` may assist in this, but probably not if you were having problems. You may need to use the Unix `kill` command to terminate the processes.
4. Run a first mpd (alone on a first node). As mentioned above, mpd uses client-server communications to perform its work. So, before running an mpd, let's run a simpler program (`mpdcheck`) to verify that these communications are likely to be successful. Even on hosts where communications are well supported, sometimes there are problems associated with hostname resolution, etc. So, it is worth the effort to proceed a bit slowly. Below, we assume that you have installed mpd and have it in your path.

Select a test node, let's call it `n1`. Login to `n1`.

First, we will run `mpdcheck` as a server and a client. To run it as a server, get into a window with a command-line and run this:

```
n1 $ mpdcheck -s
```

It will print something like this:

```
server listening at INADDR_ANY on: n1 1234
```

Now, run the client side (in another window if convenient) and see if it can find the server and communicate. Be sure to use the *same* hostname and portnumber printed by the server (above: n1 1234):

```
n1 $ mpdcheck -c n1 1234
```

If all goes well, the server will print something like:

```
server has conn on
  <socket._socketobject object at 0x40200f2c>
    from ('192.168.1.1', 1234)
server successfully recvd msg from client:
  hello_from_client_to_server
```

and the client will print:

```
client successfully recvd ack from server:
  ack_from_server_to_client
```

If the experiment failed, you have some network or machine configuration problem which will also be a problem later when you try to use mpd. Even if the experiment succeeded, but the hostname printed by the server was *localhost*, then you will probably have problems later if you try to use mpd on n1 in conjunction with other hosts. In either case, skip to Section A.2 “Debugging host/network configuration problems.”

If the experiment succeeded, then you should be ready to try mpd on this one host. To start an mpd, you will use the mpd command. To run parallel programs, you will use the mpiexec program. All mpd commands accept the -h or -help arguments, e.g.:

```
n1 $ mpd --help
n1 $ mpiexec --help
```

Try a few tests:

```
n1 $ mpd &
n1 $ mpiexec -n 1 /bin/hostname
n1 $ mpiexec -l -n 4 /bin/hostname
n1 $ mpiexec -n 2 PATH_TO_MPICH2_EXAMPLES/cpi
```


where `PATH_TO_MPICH2_EXAMPLES` is the path to the `mpich2-1.0.3/examples` directory.

To terminate the mpd:

```
n1 $ mpdallexit
```

5. Run a second mpd (alone on a second node). To verify that things are fine on a second host (say *n2*), login to n2 and perform the same set of tests that you did on n1. Make sure that you use `mpdallexit` to terminate the mpd so you will be ready for further tests.
6. Run a ring of two mpds on two hosts. Before running a ring of mpds on n1 and n2, we will again use `mpdcheck`, but this time between the two machines. We do this because the two nodes may have trouble locating each other or communicating between them and it is easier to check this out with the smaller program.

First, we will make sure that a server on n1 can service a client from n2. On n1:

```
n1 $ mpdcheck -s
```

which will print a hostname (hopefully n1) and a portnumber (say 3333 here). On n2:

```
n2 $ mpdcheck -c n1 3333
```

If this experiment fails, skip to Section A.2 “Debugging host/network configuration problems”.

Second, we will make sure that a server on n2 can service a client from n1. On n2:

```
n2 $ mpdcheck -s
```

which will print a hostname (hopefully n2) and a portnumber (say 7777 here). On n2:

```
n2 $ mpdcheck -c n2 7777
```

If this experiment fails, skip to Section A.2 “Debugging host/network configuration problems”.

If all went well, we are ready to try a pair of mpds on n1 and n2. First, make sure that all mpds have terminated on both n1 and n2. Use `mpdallexit` or simply kill them with:

```
kill -9 PID_OF_MPD
```

where you have obtained the `PID_OF_MPD` by some means such as the `ps` command.

On n1:

```
n1 $ mpd &
n1 $ mpdtrace -l
```

This will print a list of machines in the ring, in this case just n1. The output will be something like:

```
n1_6789 (192.168.1.1)
```

The 6789 is the port that the mpd is listening on for connections from other mpds wishing to enter the ring. We will use that port in a moment to get an mpd from n2 into the ring. The value in parentheses should be the IP address of n1.

On n2:

```
n2 $ mpd -h n1 -p 6789 &
```

where 6789 is the listening port on n1 (from `mpdtrace` above). Now try:

```
n2 $ mpdtrace -l
```

You should see both mpds in the ring.

To run some programs in parallel:

```
n1 $ mpiexec -n 2 /bin/hostname
n1 $ mpiexec -n 4 /bin/hostname
n1 $ mpiexec -l -n 4 /bin/hostname
n1 $ mpiexec -l -n 4 PATH_TO_MPICH2_EXAMPLES/cpi
```

where `PATH_TO_MPICH2_EXAMPLES` is the path to the `mpich2-1.3a1/examples` directory.

To bring down the ring of mpds:

```
n1 $ mpdallexit
```

7. Boot a ring of two mpds via `mpdboot`. Please be aware that `mpdboot` uses `ssh` by default to start remote mpds. It will expect that you can run `ssh` from `n1` to `n2` (and from `n2` to `n1`) without entering a password. First, make sure that you terminate the `mpd` processes from any prior tests.

On `n1`, create a file named `mpd.hosts` containing the name of `n2`:

`n2`

Then, on `n1` run:

```
n1 $ mpdboot -n 2
n1 $ mpdtrace -l
n1 $ mpiexec -l -n 2 /bin/hostname
```

The `mpdboot` command should read the `mpd.hosts` file created above and run an `mpd` on each of the two machines. The `mpdtrace` and `mpiexec` show the ring up and functional. Options that may be useful are:

- `--help` use this one for extra details on all options
- `-v` (verbose)
- `--chkup` tries to verify that the hosts are up before starting mpds
- `--chkuponly` only performs the verify step, then ends

To bring the ring down:

```
n1 $ mpdallexit
```

If `mpdboot` works on the two machines `n1` and `n2`, it will probably work on your others as well. But, there could be configuration problems using a new machine on which you have not yet tested `mpd`. An easy way to check, is to gradually add them to `mpd.hosts` and try an `mpdboot` with a `-n` arg that uses them all each time. Use `mpdallexit` after each test.

A.2 Debugging host/network configuration problems

We use `mpdcheck` as our first attempt to debug host or network configuration problems. If you run:

```
n1 $ mpdcheck --help
```

you should receive a fairly long help message describing a wide variety of arguments which can be supplied to `mpdcheck` to help you debug.

The first thing to try is to simply login to a node, say `n1` and run:

```
n1 $ mpdcheck
```

`mpdcheck` will produce no output here if it finds no problems. If `mpdcheck` does find potential problems, it will print them with `***` at the beginning of the line. You can cause `mpdcheck` to be verbose by using the `-v` option, e.g.:

```
n1 $ mpdcheck -v
```

Also, if `mpdcheck` offers comments about how you might repair certain problems, you can get a longer version of those messages by using the `-l` option, e.g.:

```
n1 $ mpdcheck -l
```

If you run `mpdcheck` on each node and find no problems, you may still wish to use it further to debug issues between two nodes. For example, you might login to `n1` and create file named `mpd.hosts` which contains the name of another node which is having trouble communicating with `n1`, e.g. `n2`. Then, you may want to run:

```
n1 $ mpdcheck -f mpd.hosts
```

This test will see if `n1` is having trouble discovering information about `n2`. If not, you wish to try:

```
n1 $ mpdcheck -f mpd.hosts -ssh
```

This will also try to test ssh support between n1 and n2.

If these 2 experiments go OK, you should probably try them again but this time logged into n2 and trying to connect back to n1. Do not forget to change the contents of mpd.hosts to contain the name of n1.

If none of these get you past the problems, you may need to ask for help. If so, it will probably useful to run mpdcheck once more on each of the nodes which are of concern:

```
n1 $ mpdcheck -pc
n2 $ mpdcheck -pc
```

These will produce quite a bit of output which may be useful in determining the problem. The -pc option does not really try to offer any comments about what may be wrong. It merely prints potentially useful debugging info.

A.3 Firewalls, etc.

If the output from any of mpdcheck, mpd, or mpdboot leads you to believe that one or more of your hosts are having trouble communicating due to firewall issues, we can offer a few simple suggestions. If the problems are due to an “enterprise” firewall computer, then we can only point you to your local network admin for assistance.

In other cases, there are a few quick things that you can try to see if there some common protections in place which may be causing your problems.

First, you might see if iptables is active. You will probably need to be root to do this:

```
n1 # iptables -L
```

This will show a set of 3 current iptables chains being applied for each of INPUT, FORWARD, and OUTPUT. If the chains are non-empty, then you may have something blocked. This could be a result of a software firewall package you are running (e.g. shorewall) or some home-grown set of chains. If you are unfamiliar with iptables, you will need to get local help to decipher the rules and determine if any of them may be affecting you. There are options such as -F to iptables that will disable the chains, but that is dangerous of course if you require them for protection.

Next, you might see if any tcp-wrappers are active. You may need to be root to do this:

```
n1 # cat /etc/hosts.deny /etc/hosts.allow
```

If there are any uncommented lines, they likely designate any (or ALL) daemons which have their tcp communications blocked. This can be particularly problematic for mpdboot which uses ssh (and thus the ssh daemon, sshd).

Next, you might wish to see if you have available ephemeral ports:

```
n1 $ cat /proc/sys/net/ipv4/ip_local_port_range
```

This should print a range something like:

```
32768    61000
```